

Cement Mill Test Report

Date of Issue: May 12, 2021

Plant: Product: Mill Test Report Number: Manufactured: Exshaw, AB Portland Cement Type III MTR-III-2021-04 April 1-30, 2021

ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

CHEMICAL ANALYSIS			PHYSICAL ANALYSIS			
Item	Spec limit	Test Result	Item	Spec limit	Test Re	sult
Rapid Method, X-Ray (C114))		Air content of mortar (%) (C185)	12 max	6	
SiO ₂ (%)		19.6				
Al ₂ O ₃ (%)		3.9	Blaine Fineness (m ² /kg) (C204)		628	
Fe ₂ O ₃ (%)		3.7				
CaO (%)		61.8	Passing 45 μm (%) (C430)		99.2	
MgO (%)	6.0 max	4.6				
SO ₃ (%)	3.5 max	3.3	Autoclave Expansion (%) (C151)**	0.80 max	0.07	
Loss on Ignition (%)	3.5 max	2.4				
Insoluble Residue (%)**	1.5 max	0.09	Compressive strength (MPa, [psi]) (C109)			
CO ₂ (%)		1.7	1 day	12.0 [1740] min	26.6	[3860]
Limestone (%)	5.0 max	3.9	3 days	24.0 [3480] min	35.8	[5190]
CaCO ₃ in Limestone (%)	70 min	98	28 days (Reflects previous month's data))	50.3	[7290]
Inorganic Process Addition	5.0 max	-				
(Lafarge Cement Kiln Dust)						
			Time of setting (minutes)			
Adjusted Potential Phase Composition (C150)			Vicat Initial <i>(C191)</i>	45 - 375	52	
C ₃ S (%)		53				
C ₂ S (%)		16				
C ₃ A (%)	15 max	4				
C₄AF (%)		11				
ASTM C 150-17 and AASHTC	O M 85-17 Optior	nal Chemical Require	ments:			
NaEq (%)	0.60 max	0.55				

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of ASTM C 150-20 & AASHTO M 85-18 STANDARD SPECIFICATIONS FOR TYPE III CEMENT; and ASTM C 150-20 & AASHTO M 85-18 OPTIONAL CHEMICAL REQUIREMENTS FOR TYPE III LOW ALKALI CEMENT.

Certified By:

Lorraine Richards

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, TOL 2C0 Phone: 403-673-3815

Lorraine Richards Quality Control Coordinator



Cement Mill Test Report

Date of Issue: May 12, 2021

Plant: Product: Mill Test Report Number: Manufactured: Exshaw, AB Portland Cement Type III MTR-III-2021-04 April 1-30, 2021

ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

Additional Data

Item	Test Result		
	Limestone	Inorganic Process Addition	
		Lafarge Cement Kiln Dust	
Amount (%)	3.9	-	
SiO ₂ (%)	0.4	n/a	
Al ₂ O ₃ (%)	0.3	n/a	
Fe ₂ O ₃ (%)	0.2	n/a	
CaO (%)	52.5	n/a	
SO ₃ (%)	0.1	n/a	
CO ₂ (%)	43.1	n/a	

Base Cement Phase Composition

Item	Test Result
C ₃ S (%)	56
C ₂ S (%)	17
C ₃ A (%)	4
C₄AF (%)	12

We certify that the data above reflects the materials used in cement manufacture during the production period indicated.

Note: Specifc Gravity for Portland Cements is 3.15

Certified By:

Lorraine Richards

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, T0L 2C0 Phone: 403-673-3815

Lorraine Richards Quality Control Coordinator