

#### Cement

## **FLY ASH TEST REPORT**

Analysis by: Lafarge Seattle Concrete Lab

Sample from : Centralia Power Plant

Average Analysis: May 2021 Test Report Number 6-21 Class F

## **Chemical Analysis**

	Results	Limits
Silicon Dioxide (SiO <sub>2</sub> )	47.9 %	
Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	16.6 %	
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	5.8 %	
Total $(SiO_2) + (Al_2O_3) + (Fe_2O_3)$	70 %	50% Min - ASTM
Sulphur Trioxide (SO <sub>3</sub> )	1.0 %	5% Max - ASTM
Calcium Oxide (CaO)	15.0 %	18% Max - ASTM
Magnesium Oxide	5.6 %	
Moisture Content	0.15 %	3% Max - ASTM
Loss on Ignition	0.29 %	5% Max
Available Alkali as Equiv. Na <sub>2</sub> 0 (previous month's result)	0.52 %	1.5% Max

## **Physical Analysis**

Fineness Retained on 45 um (No. 325 Sieve)	20.0 %	34% Max - ASTM
Strength Activity Index with Portland Cement		
% of Control at 7 Days	88 %	75% Min - ASTM
% of Control at 28 Days (previous month's result)	92 %	75% Min - ASTM
Water Requirement, Percent of Control	93 %	105% Max- ASTM
Autoclave Expansion	0.05 %	0.8% Max - ASTM
Density	2.64 Mg/m <sup>3</sup>	

#### **Uniformity Requirements**

Density, Variation from Average	0.00 %	5% Max - ASTM
Fineness 45um Sieve, Variation from Average	2.30 %	5% Max - ASTM

We hereby certify that the composite fly ash sample above meets the chemical and physical requirements of ASTM C618 and AASHTO M295 for class F fly ash.

Certified : \_

Rob Shogren Technical Director

# WESTERN REGION

5400 West Marginal Way SW, Seattle, Washington 98106-1517 Office: 206.923.0098 or 800.477.0100 Fax: 206.923.0388