

# Cement Mill Test Report

Date of Issue: August 16, 2021

Plant: Product: Mill Test Report Number: Manufactured:

Exshaw, AB Portland Cement Type III MTR-III-2021-07 July 1-31, 2021

## ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

CHEMICAL ANALYSIS			PHYSICAL ANALYSIS			
Item	Spec limit	Test Result	Item	Spec limit	Test Re	sult
Rapid Method, X-Ray (C114)	)		Air content of mortar (%) (C185)	12 max	4	
SiO <sub>2</sub> (%)		19.7				
Al <sub>2</sub> O <sub>3</sub> (%)		4.0	Blaine Fineness (m <sup>2</sup> /kg) (C204)		608	
Fe <sub>2</sub> O <sub>3</sub> (%)		3.7				
CaO (%)		61.9	Passing 45 μm (%) (C430)		99.6	
MgO (%)	6.0 max	4.5				
SO <sub>3</sub> (%)	3.5 max	3.3	Autoclave Expansion (%) (C151)**	0.80 max	0.08	
Loss on Ignition (%)	3.5 max	2.6				
Insoluble Residue (%)**	1.5 max	0.33	Compressive strength (MPa, [psi]) (C1	Compressive strength (MPa, [psi]) (C109)		
CO <sub>2</sub> (%)		1.8	1 day	12.0 [1740] min	25.7	[3720]
Limestone (%)	5.0 max	4.3	3 days	24.0 [3480] min	35.6	[5170]
CaCO <sub>3</sub> in Limestone (%)	70 min	96	28 days (Reflects previous month's data)		52.1	[7550]
Inorganic Process Addition	5.0 max	-				
(Lafarge Cement Kiln Dust)						
			Time of setting (minutes)			
Adjusted Potential Phase Composition (C150)			Vicat Initial <i>(C191)</i>	45 - 375	82	
C <sub>3</sub> S (%)		53				
C <sub>2</sub> S (%)		16				
C <sub>3</sub> A (%)	15 max	4				
C₄AF (%)		11				
ASTM C 150-17 and AASHTC	O M 85-17 Optior	al Chemical Require	ments:			
NaEq (%)	0.60 max	0.54				

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of ASTM C 150-20 & AASHTO M 85-18 STANDARD SPECIFICATIONS FOR TYPE III CEMENT; and ASTM C 150-20 & AASHTO M 85-18 OPTIONAL CHEMICAL REQUIREMENTS FOR TYPE III LOW ALKALI CEMENT.

Certified By:

Lorraine Richards

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, TOL 2C0 Phone: 403-673-3815

Lorraine Richards Quality Control Coordinator



# **Cement Mill Test Report**

Date of Issue: July 13, 2021

Plant: Product: Mill Test Report Number: Manufactured: Exshaw, AB Portland Cement Type III MTR-III-2021-07 July 1-31, 2021

### ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

#### **Additional Data**

Item	Test Result			
	Limestone	Inorganic Process Addition		
		Lafarge Cement Kiln Dust		
Amount (%)	4.3	-		
SiO <sub>2</sub> (%)	0.9	n/a		
Al <sub>2</sub> O <sub>3</sub> (%)	0.7	n/a		
Fe <sub>2</sub> O <sub>3</sub> (%)	0.2	n/a		
CaO (%)	51.4	n/a		
SO <sub>3</sub> (%)	0.2	n/a		
CO <sub>2</sub> (%)	42.4	n/a		

#### **Base Cement Phase Composition**

Item	Test Result
C <sub>3</sub> S (%)	55
C <sub>2</sub> S (%)	17
C <sub>3</sub> A (%)	5
C₄AF (%)	12

We certify that the data above reflects the materials used in cement manufacture during the production period indicated.

Note: Specifc Gravity for Portland Cements is 3.15

Certified By:

Lorraine Richards

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, T0L 2C0 Phone: 403-673-3815

Lorraine Richards Quality Control Coordinator