

Cement Mill Test Report

Date of Issue: July 13, 2022

Plant: Exshaw, AB

Product: Portland Cement Type III

Mill Test Report Number: MTR-III-2022-06
Manufactured: June 1-30, 2022

ASTM C 150-21 and AASHTO M 85-18 Standard Requirements

CHEMICAL ANALYSIS			PHYSICAL ANALYSIS			
Item	Spec limit	Test Result	Item	Spec limit	Test Re	sult
Rapid Method, X-Ray (C114)			Air content of mortar (%) (C185)	12 max	6	
SiO ₂ (%)		19.5				
Al ₂ O ₃ (%)		4.0	Blaine Fineness (m²/kg) (C204)		578	
Fe ₂ O ₃ (%)		3.6				
CaO (%)		62.0	Passing 45 μm (%) (C430)		99.0	
MgO (%)	6.0 max	4.8				
SO ₃ (%)	3.5 max	3.3	Autoclave Expansion (%) (C151)**	0.80 max	0.17	
Loss on Ignition (%)	3.5 max	2.6				
Insoluble Residue (%)**	1.5 max	0.26	Compressive strength (MPa, [psi]) (C1)	09)		
CO ₂ (%)		1.9	1 day	12.0 [1740] min	26.9	[3910]
Limestone (%)	5.0 max	4.5	3 days	24.0 [3480] min	39.0	[5650]
CaCO ₃ in Limestone (%)	70 min	86	28 days (Reflects previous month's data)		53.6	[7770]
Inorganic Process Addition (Lafarge Cement Kiln Dust)	5.0 max	-				
			Time of setting (minutes)			
Adjusted Potential Phase Composition (C150)			Vicat Initial (C191)	45 - 375	82	
C ₃ S (%)		56				
C ₂ S (%)		14				
C ₃ A (%)	15 max	4				
C ₄ AF (%)		11				
ASTM C 150-17 and AASHTO	M 85-17 Option	nal Chemical Require	ments:			

ASTM C 150-17 and AASHTO M 85-17 Optional Chemical Requirements: NaEq (%) 0.60 max 0.56

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of ASTM C 150-21 & AASHTO M 85-18 STANDARD SPECIFICATIONS FOR TYPE III CEMENT; and ASTM C 150-21 & AASHTO M 85-18 OPTIONAL CHEMICAL REQUIREMENTS FOR TYPE III LOW ALKALI CEMENT.

Certified By:

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, T0L 2C0

Phone: 403-673-3815

Lorraine Richards Quality Manager

Lorraine Richards



Cement Mill Test Report

Date of Issue: July 13, 2022

Plant: Exshaw, AB

Product: Portland Cement Type III

Mill Test Report Number: MTR-III-2022-06
Manufactured: June 1-30, 2022

ASTM C 150-21 and AASHTO M 85-18 Standard Requirements

Additional Data

Item	Test Result			
	Limestone	Inorganic Process Addition		
		Lafarge Cement Kiln Dust		
Amount (%)	4.5	-		
SiO ₂ (%)	1.1	n/a		
Al ₂ O ₃ (%)	0.7	n/a		
Fe ₂ O ₃ (%)	0.2	n/a		
CaO (%)	50.7	n/a		
SO ₃ (%)	0.1	n/a		
CO ₂ (%)	42.3	n/a		

Base Cement Phase Composition

Item	Test Result
C ₃ S (%)	58
C ₂ S (%)	14
C ₃ A (%)	4
C ₄ AF (%)	11

We certify that the data above reflects the materials used in cement manufacture during the production period indicated.

Note: Specifc Gravity for Portland Cements is 3.15

Certified By:

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, TOL 2C0

Phone: 403-673-3815

Lorraine Richards

Lorraine Richards Quality Manager