

Mill Test Report Number: SEA\_NEWCEM\_July2023

YEAR: 2023

MONTH OF PRODUCTION: June

PLANT: Seattle

**CEMENT TYPE: NewCem Grade 100** 

Reference Cement				
Fineness by Air Permeability (m²/kg; ASTM C204)	393			
Fineness by 45 µm (No. 325) Sieve (% retain; ASTM C430)	3.2			
Compressive Strength				
(ASTM C109/C109 M) 7-day 28-day	<b>psi</b> 4,640 5,900	Min Limit - 5,000		
Total Alkalies (Na <sub>2</sub> O + 0.658 K <sub>2</sub> O) (%, ASTM C114)	Actual 0.8	<u>Limits</u> 0.6-0.9		

Percent
32.8
1.1
13.6
40.2
5.3
4.5
0.78
0.61
1.6

	Slag		
Fineness by Air Permeability (m²/kg; ASTM C204)	411		
Fineness by 45 µm (No. 325) Sieve (% retain; ASTM C430)	6.2		
Compressive Strength (ASTM C109/C109 M)		<u>SAI</u>	SAI Limit <u>Min</u>
28-day (Previous Month)		102	95
Specific Gravity (Mg/m³; ASTM C188)	2.88		
	<u>Actual</u>	Max	Limit
Air Content of Mortar (%, ASTM C185)	5.9	12	
Sulfide Sulfur (% S, ASTM C114)	0.8	2.5	
Sulfate Ion (% as SO3, ASTM C114)	4.5	Α	
Autoclave expansion (%, CSA A3004-B5)	-0.020	0.5	
Color Value L*	83.0		

The ground granulated blast furnace slag complies with the current specification of the chemical physical requirement of ASTM C-989, AASHTO M-302 for grade 100 Ground Granulated Blast Furace Slag (GGBFS) and and CSA A3001 Slag.

Slag source is JFE Mineral Company in Kurashiki City, Japan. NewCem is ground and manufactured in Seattle, WA.



Certified by:

Rob Shogren Techincal Director

July 3, 2023

A. D. Shogen

A Not Applicable.